# SBS Self-Adhering Roofing System

## **Owner's Best Choice**

- Safer For Your Building... Self-adhering membrane systems eliminate the need for open flames on your roof.
- *No Fumes...* Unlike conventionally applied systems, eliminates the fumes and odors caused by hot asphalt or solvent-based adhesives.
- *Proven Technology...* Based on the same technology used in GAF's commercial modified bitumen roofing systems—proven in the field for decades!
- *Great Warranty...* Free ltd. system warranty against material defects for up to 15 years.\*
- *Extended Guarantees Available...* Optional full-system guarantees against manufacturing defects and workmanship errors available for up to 20 years.\*\*
- *Peace Of Mind...* Backed by GAF, North America's largest roofing manufacturer.
- Seven Popular Colors... To complement your Timberline<sup>®</sup> or other residential shingle roof.

## **Professional's Best Choice**

- Safer For Your Installers... No torches, kettles, or dangerous chemicals—may even reduce your insurance premiums!
- *Quicker Installation...* Often 1/3 faster than conventional systems, with minimal set-up or clean-up time.
- No Extra Tools... No need to stage expensive equipment.
- *Proven Technology...* Based on the same technology as GAF's RUBEROID<sup>®</sup> SBS modified bitumen membranes.
- Flexible Installation Options

#### Color Palette



*Note:* These blended colors are designed to complement your shingles, not to be an exact match. Because of the small size of these samples, it is difficult to reproduce the actual color effect. Please be sure to see a full-size roll before making a final color selection.

\*See LIBERTY<sup>™</sup> Limited Warranty On SBS Materials for complete coverage and restrictions. \*\*See System Pledge<sup>™</sup> Roof Guarantee and RUBEROID®/GAFGLAS® Diamond Pledge<sup>™</sup> NDL Roof Guarantee for complete coverage and restrictions.



0.1.



#### **Applicable Standards:**

Open

IIMes

- FM Approved
- UL Classified
- Miami-Dade County Product Control Approved
- FBC Approved
- Texas Department of Insurance\*
- \* Texas Department of Insurance does not apply to LIBERTY<sup>™</sup> MA Base Sheet

### **Product Specifications (Nom.)**

#### LIBERTY<sup>™</sup> MA Base Sheet

Roll length	
0	
	0.068 in (1.73 mm)
0	2 squares, 216 sq ft (20.1 m <sup>2</sup> )

#### LIBERTY<sup>™</sup> Self-Adhering Base/Ply Sheet

Dase/1 Ty Sheet	
Roll length	
Roll width	39.375 in (1.0 m)
Roll thickness	0.068 in (1.73 mm)
Roll weight	82 lbs (37.2 kg)
Roll size 2 squa	res, 216 sq ft (20.1 m <sup>2</sup> )

## LIBERTY<sup>™</sup> Self-Adhering

Cap Sneet	
Roll length	34.0 ft (10.4 m)
Roll width	
Roll thickness	0.157 in (4.0 mm)
Roll weight (Cap Sheet).	96.4 lbs (43.7 kg)
Roll size 1 squa	re, 112 sq ft (10.4 $m^2$ )